

Exit Door with Wireless Wall Reader



ASSA ABLOY

Solution family: Interior/Exterior door solutions
Solution group: Double-Steel-Self Closing-
Panic Device-Access Control

Description

ASSA ABLOY Spain's solution for Evacuation Route with Wall Reader for access monitoring (the wall reader unblocks the electromagnetic lock). Free exit via the activation of the panic exit bar with micro in one single.

The management of the wireless communication is carried out via SMARTair™ Hubs. These hubs are able to manage up to 30 access points, depending on their location and placement.

Typical application markets

For all kinds of buildings, particularly Hospitals, Hotels, Offices, Institutional Buildings, Stations, Airports and Leisure Spots

Hardware set

- Panic exit rim sliding device with one lateral locking point. Includes Micro. TESA's TOP series, Standard: EN 1125
- Panic exit rim sliding device on passive leaf with two bolt locking points. Includes Micro. TESA's TOP series, Standard: EN 1125
- Patented security cylinder, TESA's TX80, Standard: EN 1303
- Handle with keyhole for panic exit rim devices and blind plate on passive leaf, TESA's SENA series, AISI 316 quality, Use Category: 3, Standard: EN1906
- Electromagnetic rim lock
- ASSA ABLOY Cam-Motion® DC 500 door closer and guide, Standard: EN1154, DDA/CEN PR 15894, EN 15804 (EPD-ASA-20130275-IBC1-EN)
- Mortise cable grommet



Exterior



Interior